



MODEL: CT2710C-LT-SL

SPECIFICATIONS

DESCRIPTION

MODEL – CT2710C-LT-SL
GVWR – 9,850 lbs.
Empty Weight – 6,300 lbs.
Carrying Capacity – 3,200 lbs.
Overall Length – 27 ft.
Overall Width – 96 in.
Overall Height – 8 ft. – 4 in.
Maximum Coil OD – 125 in.
Minimum Coil ID – 48 in.
Maximum Width – 66 in.

RUNNING GEAR

Dual Axle – 5,200 lbs. Each
Brakes – Electric
Tires – ST225/75R15 LRD
Wheels – 15 x 6 6 Bolt Mod
Suspension – Slipper Leaf Spring



FRAME

Main Frame – Double Frame – 8 x 2 x 3/16" Tube
6 x 4 x 3/16" Tube
Coil Cage – 2 x 2 x 1/4" Square Tube
Mast Uprights Inside – 6 x 2 x 3/8" Rect. Double Tube
Mast Uprights Outer – 7 x 5 x 3/16" Rect. Tube
Mast Rollers – 5" Sch. 40 Pipe
Threading Rollers – 3 1/2" Sch 40 Pipe
Interior Roller – 3 1/2" Sch 40 Pipe
Tongue – 6 x 4 x 3/16" Tube with Adjustable Pintle Eye
Fenders – 12 ga.

ELECTRICAL

Plug – 7 RV Molded Plug
Wiring – Enclosed in Tube with Junction Box
Lights – Standard LED

SAFETY

Chains – 3/8" with Heavy Duty Hook & Safety Latch
Breakaway – Battery, Battery Box and Switch
Decals – Warning Decals and Reflective Tape

INCLUDED ACCESSORIES

McElroy 4-6 in. LineTamer® (LT0048)
Toolbox – Black Aluminum Diamond Plate

FINISH

Polyurethane Enamel

HYDRAULICS

Motor – 5.5 HP Honda Motor
Hydraulic Winch
Valve – One 2 Spool Valve and One 3 Spool Valve
Hydraulic Mast Cylinder – 4 x 36 in. Tie Rod
Hydraulic Arm Cylinder – 5 x 24 in. Tie Rod
Interior Roller Cylinder – 2 x 12 in. Tie Rod
Threading Roller Cylinder – 2 1/2 x 6 in. Tie Rod

AVAILABLE OPTIONS

Optional McElroy 2" LineTamer® (LT0122)
Optional 2" LineTamer® Mount (LTM2)
Optional 3" Re-Round Kit (LT0037)
Optional Bulldog Collar – LOK 2 5/16" Coupler

